

## 10 Zone Call Controller c/w 300mA PSU (Flush Version)

Part No. **NC910F**



### Overview

- Compatible with C-TEC's entire range of 800 Series field devices.
- Housed in an attractive flush mounting plastic enclosure measuring just 214mm x 178mm
- Two call levels - standard (constant tone) and emergency (intermittent tone).
- Optional mute and call accept/reset buttons.
- 'Call Accept' functionality allows staff to send an intermittent call acknowledgment signal to calling zones to confirm help is on the way (dependent on wiring and field devices used).
- Includes a 12V 300mA PSU and 2 volt-free relay contacts which activate on a standard or emergency call.
- Innovative slide-in labelling system.
- Zones can be wired in 4 or 6 core (7/02) stranded security cable.
- Additional zone controllers and expansion units available for use as repeaters on larger sites.
- Optional boxed PSUs c/w with space for a 12V VRLA battery available for sites where a standby battery facility is required.



### Technical Specifications

|                       |                                                                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Mains supply          | 230V 50/60Hz. (36mA max. current).                                                                                                                  |
| Internal power supply | 11V d.c. (300mA max. current when powered by Mains).                                                                                                |
| Quiescent current     | 0mA (none).                                                                                                                                         |
| Alarm current         | Determined by the number/type of field devices connected to the call controller/system.                                                             |
| Auxiliary relays      | 2 volt free relay contacts (NO/C/NC). Activate when a standard or emergency call is received by the controller. Both relays rated at 30V d.c. @ 1A. |



|                                    |                                                                                                                                                                                                      |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Auxiliary inputs                   | External PSU Input: 9V-15V d.c. @ 400mA (suitable for use with an BF560-12 12V 2A boxed PSU which has space available for a 12V 7AH battery).                                                        |
| Indicators                         | Green Power on LED; 10 x red Zonal Alarm LEDs (lit steady for a Standard call, pulse for an Emergency call); Internal buzzer (on steady for any Standard call, intermittent for any Emergency call). |
| Controls                           | 2 Buttons - (A) Reset or inactive ; (B) 'Mute' or 'Call Accept'. (Both buttons are link selectable). If Call Accept is selected indicators on relevant field devices will emit an intermittent tone. |
| Expansion connections              | CONN2 allows the connection of 1 x NC910EF 10 Zone Expansion Unit or 1x NC920EF 20 Zone Expansion Unit.                                                                                              |
| Call acknowledgement functionality | Yes.                                                                                                                                                                                                 |
| Product dimensions (mm)            | 214 W x 178 H x 70 D mm (overall). Hole required for flush mounting is 176 W x 162 H x 55 D mm.                                                                                                      |
| Construction & finish              | Plastic detachable lid and back box. RAL7035.                                                                                                                                                        |
| IP Rating                          | IP41.                                                                                                                                                                                                |
| Weight                             | 1.27kg.                                                                                                                                                                                              |
| Operating conditions/temperature   | -5°C to +40°C. Max. relative humidity 95% non-condensing.                                                                                                                                            |

