

## Evacuation Alert System Mains Isolator Keyswitch

Part No. **EAP326/WS**



### Overview

- Allows the mains to an Evacuation Alert panel to be switched on or off.
- Supplied with a surface mounting back box.
- Third-party tested to the relevant insulation and isolation requirements of IEC/EN 60669.
- Double pole.
- Fitted with a 5A Fuse.
- Supplied with a special key that is only available to the responsible person.
- Able to be wired with 1 x 2.5mm<sup>2</sup> cable or 2 x 1.5mm<sup>2</sup> cable to ensure only independent sole main supplies are used to the Evacuation Alert panel.



### Technical Specifications

|                                  |                                                                                                  |
|----------------------------------|--------------------------------------------------------------------------------------------------|
| Approvals/certifications         | Third-party tested to the relevant insulation and isolation requirements of IEC/EN 60669         |
| Type                             | Double pole, lockable, 230V                                                                      |
| Mains rated current              | 5A.                                                                                              |
| Supply/operating voltage         | 230 VDC.                                                                                         |
| Quiescent current                | 2mA if LED, 0mA if no LED,                                                                       |
| IP Rating                        | IP30.                                                                                            |
| Operating conditions/temperature | -5°C to +40°C. Max. relative humidity 95% non-condensing.                                        |
| Construction & finish            | White PVC.                                                                                       |
| Product dimensions (mm)          | Switch Plate 86 x 86 mm x 25 or (25.7mm deep with LED), with supplied back box fitted 54mm deep. |
| Weight                           | TBC.                                                                                             |



Notes

Key type: Red C-TEC S-Key.

