

ActiV Diode Base

Part No. **C4408D**



Overview

- Compatible with C-TEC's entire range of ActiV fire detectors.
- Third-party certified to the relevant parts of EN54 in conjunction with our ActiV detectors.
- Easy to fit with lots of working space.
- Can be ceiling mounted in any orientation due to the true 360° degree viewing angle of the LED indicator strips on all ActiV detectors.
- Integrated detector/base locking mechanism, head removal tool and ID tag.
- Simple 'click and twist' design.
- Remote LED terminals for the optional connection to a BF318 Remote indicator.
- C4408 non-diode and C4408R relay bases also available.



Technical Specifications

Approvals/certifications	Certified to the relevant parts of EN54 by Intertek as part of our ActiV fire detector certifications
Supply wiring	2-wire monitored, polarity sensitive.
Connections	(1) +V In; (2) +V Out; (3) Remote LED +V; (4) 0V; (5) 0V; (6) Screen; (7) Screen. Schottky diode connected between 1 & 2. Terminals can accept up to 2.5mm fire rated cable.
Product dimensions (mm)	102.2mm diameter x 20.5mm deep.
Construction & finish	White polycarbonate rated to UL94 V-2 with bright tin plated steel terminals fitted with nickel plated steel screws/washers.



Weight

55g.

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK
Telephone: **01942 322744**
Email: sales@c-tec.co.uk
c-tec.com

You're Safe with C-TEC

