

## Emergency Only Call Point, Button Reset

Part No. **NC804DE**



### Overview

- A button-operated call/reset point capable of generating Emergency calls on an 800 Series Call System.
- Onboard reset button cancels Emergency calls made from the NC804DE **and** Standard calls made from other devices wired on the same zone (such as ceiling pull units in Ensuite areas).
- Ideal for use as a reset point for ceiling pull units that will allow a more urgent Emergency call to be made if additional assistance is required.
- Red reassurance LED confirms a call has been made.
- Mounts on a standard UK 25mm single gang flush or surface back box.



### Technical Specifications

|                                   |                                                                                                                                                              |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Quiescent current                 | 0mA (none).                                                                                                                                                  |
| Alarm current                     | Determined by the type of control equipment and number / type of field devices connected to the system.                                                      |
| Indicators                        | Red Reassurance LED (lit intermittently for Emergency calls made on the NC804DE and constantly for Standard calls made from other devices on the same zone). |
| Controls                          | Alert button (generates Emergency calls); Reset button (cancels Emergency calls from the NC804DE or Standard calls from devices wired on the same Zone).     |
| Connections                       | SIG (Signal); -Ve (Negative); +Ve (Positive).                                                                                                                |
| Onboard 6.35mm Remote Jack Socket | No.                                                                                                                                                          |
| Onboard Infrared Receiver         | No.                                                                                                                                                          |
| Product dimensions (mm)           | 87 W x 87 H x 24 D mm. Mounts on a UK 25mm single gang back box.                                                                                             |
| Construction & finish             | Plastic.                                                                                                                                                     |



|                                  |                                                           |
|----------------------------------|-----------------------------------------------------------|
| IP Rating                        | IP40.                                                     |
| Weight                           | 58g                                                       |
| Operating conditions/temperature | -5°C to +40°C. Max. relative humidity 95% non-condensing. |

