

ActiV Conventional Weatherproof Hi-Output 100dB(A) Wall Sounder (IP55)

Part No. **BF430C/CC/DR/65**



Overview

- Third-party certified to EN54-3 (Sounders).
- Impressive 100dB(A) sound output @ 1m.
- Includes 31 selectable primary tones and an optional secondary tone.
- Two volume levels (high and low)
- Max. Alarm Current at 30Vdc = 6mA.
- Typical Alarm Current at 30Vdc = 4mA.
- IP55C rated (weatherproof).
- Manufactured in the UK by C-TEC.



Technical Specifications

Approvals/certifications	Certified to EN54-3 by the LPCB
Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be wall mounted. Weatherproof to IP55C.
VAD category & coverage	N/A.
Flash rate & colour	N/A.
Supply/operating voltage	18 to 30V DC.
Nominal SPL (Sound Pressure Level)	100dB(A).



Alarm current	Max. @ 30Vdc = 6mA; Typ. @ 30Vdc = 4mA.
Product dimensions (mm)	114mm diameter x 132mm deep.
IP Rating	IP55C (Weatherproof).
Weight	315g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).

