

Hush-Pro Landlord System Interface (Apollo XP95/Discovery Protocol)

Part No. **HP733/XP**



Overview

- Compatible with C-TEC's Apollo XP95/Discovery protocol ZFP addressable fire panels.
- Allows a stand-alone [Hush-Pro domestic fire alarm system](#) to be connected to a ZFP Apollo XP95/Discovery landlord/communal system to unlock a series of powerful optional features such as remote off-site monitoring via the Cloud, automatic evacuation of dwellings in a Fire Level 2 condition, manual keyswitch evacuations by the fire and rescue services and more.
- Visit our [Domestic Fire Systems](#) section for more information on Hush-Pro - a new approach to integrating domestic and communal/landlord fire alarm systems.

For availability details email hush-pro@c-tec.co.uk

Technical Specifications

Protocol/compatibility	Allows Hush-Pro domestic fire alarm systems to be connected to C-TEC ZFP Apollo XP95/Discovery fire alarm panels.
Power requirements	Loop powered (individual Hush-Pro Controllers/Systems are powered by their own PSUs).
Quiescent current	TBC.
Indicators	Local Fire (Fire Level 1), Global Fire (Fire Level 2), Fault (from Hush-Pro Controller) and Loop Fault.
Product dimensions (mm)	146 W x 85 H x 21 D mm (Can be mounted on a standard UK 25mm double gang flush or surface back box).
Construction & finish	Supplied on a double gang plastic plate.
IP Rating	IP40.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.
Notes	More detailed tech specs to follow.