

## Hi-Output Wall Voice Sounder (shallow base)

Part No. **BF446A/CX/SR**



### Overview

- Superb sound intelligibility.
- Includes three selectable voice message pairs.
- Includes the same electronics as our EN54-3 & 17 certified Wall Sounder.
- Onboard short-circuit loop isolator.
- 550 $\mu$ A quiescent current.
- 10mA alarm current @24V DC (voice sounder on max).
- Group addressing facility allows multiple devices to be operated simultaneously.
- 7 selectable volume levels and up to 15 selectable tone pairs.
- IP21C (Type A) rated.

### More Information

### Technical Specifications

Protocol/compatibility	Compatible with C-TEC's XFP/ZFP XP95/Discovery Addressable Fire Panels.
Application/operation	Designed to be wall mounted. Indoor areas only.
VAD category & coverage	N/A.
Flash rate & colour	N/A.
Supply/operating voltage	17 to 28V DC.
Quiescent current	550 $\mu$ A @ 24 VDC.
Nominal SPL (Sound Pressure Level)	89 dB(A) @ 1 m
Alarm current	10mA (Voice Sounder on max).



Indicators	Polling (green LED) & Short Circuit Isolator Active (amber LED).
Product dimensions (mm)	108mm diameter x 99mm deep
IP Rating	IP21C (Type A).
Weight	215g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).
Notes	Includes the same electronics as our EN54-3 & 17 certified Hi-Output Wall Sounder.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom