

ZFP Touchscreen Control Module, Apollo protocol

Part No. **Z41**



Overview

- Supplied as standard in all pre-built ZFP Apollo panels and all core ZFP Apollo panels.
- Includes a user-friendly full-colour 4.3 inch 480 x 272 pixel LCD touchscreen.
- Separate distinct LEDs for mandatory EN54 indications plus five spare engineer programmable LEDs.
- Keyswitch or dynamic touchscreen button access to AL2 (Authorised User Level).
- Digital QWERTY keyboard.
- Touchscreen can be customised to include a company logo (.gif)
- Galvanically isolated USB port (for system programming).
- Indicator naming template (Microsoft Word format) downloadable from the Documentation tab below.



More Information

Technical Specifications

Compatibility	One required per ZFP standard, medium or large panel (supplied as standard on all pre-built ZFP panels and all core ZFP panels).
Protocol/compatibility	Apollo.
Indicators	Full-colour 480 x 272 pixel touchscreen; 16 LEDs (11 reserved for mandatory EN54 indicators plus 5 engineer programmable indicators).



Controls	Interactive touchscreen with menu sensitive buttons; 1 x keyswitch allowing direct access to Access Level 2. Keyswitch requires S-KEY fire panel key.
Product dimensions (mm)	180 W x 170 H x 20 D mm.
Construction & finish	Plastic.
Weight	TBC.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom